

Tehnička specifikacija za agregat Kipor KDE 16SS Monofazni

| | |
|--|---|
| Frekvencija - f u Hertzima / Rated frequency (Hz) | 50 Hz |
| Snaga u kVA (kilovolt amperima) / Rated output(kVA) | 16 kVA |
| Snaga u kilovatima (kW) / Max. ouput (kW) | 13 kW |
| Izlazni napon u V (Voltima) / Rated voltage (V) | 230 V |
| Maksimalna struja u A (Amperima) /Rated current (A) | 56.5 A |
| Brzina / Rated speed (r/min) | 1500 |
| Faze / Phase NO. | Monofazna / Single-phase |
| Faktor snage / Power factor (cosφ) | 1.0 |
| Izolacija / Insulation grade | High |
| Prijenos struje | Bez četkica i permanentnih magneta / Brushless Self-excitation(AVR) |
| Vrsta ekrana / Panel type | Digitalni ekran / Digital Panel |
| Voltaža / Volage | 230 V |
| Utičnice / Receptacle | Dvije monofazne shuko utičnice / Twe shuko plugs |
| Repovi / Connection pole | Da / With |
| DC12V izlaz / output | Ne / Without |
| Dimenzije agregata (D×Š×V u mm) / Overall dimension (L×W×H mm) | 1570×780×1050 mm |
| Težina bez goriva i ulja (kg) / Dry weight (Kg) | 720 kg |
| Težina stroja spremnog za rad (kg) / Working assorting weigh(Kg) | 790 kg |
| Razina buke na 7 metara udaljenosti (dB) / Noise Level(7M) db(A) | 51 dB |
| Zvučna izolacija / Structure type | Ultra tih / Ultra silent |
| Model motora / Engine Model | KD488 |
| Tip motora / Engine type | Četvero cilindrični, redni, 4-ero taktni, direkt. ubrizg. / Four-cylinder, in-lined, four-strok, direct injection. |
| Promjer×hod cilindra / bore×stroke cylinder(mm) | 88×90 mm |
| Zapremina / Displacement | 2190 |
| Snaga motora u kW / Rated engine power (kW / (r/min) | 16.4 kW pri 1500 rpm / 16.4 kW at 1500 rpm |
| Kompresija / Compression ratio | 18.2:1 |
| Max. broj obrtaja / Rated rotation speed | Broj okretaja u minuti / Rotation per minute |
| Sistem paljenja / Starting system | Elektro starter / Electric starter |
| Sistem hlađenja / Cooling system | Vodeno hlađenje / Water cooled |
| Sistem podmazivanja / Lubrication system | Uljna pumpa / Pressure splash |
| Vrsta goriva / Fuel type | Dizel / Diesel |
| Ulje za podmazivanje / Lube oil | 10W-30,15W-40 |
| Kapacitet vode za hlađenje / Capacity of cooling Water(L) | 12 l |
| Kapacitet ulja / Lube capacity (L) | 8,5 l |
| Snaga anlasera pri 12 V / Starting motor capacity (V-kW) | 12V 1.4kW |
| Kapacitet punjača akumulatora-alternatora / Charging generator capacity | 12V 15A |
| Kapacitet akumulatora / Battery capacity(V-Ah) | 12V 65Ah |
| Potrošnja goriva / Fuel consumption (g/kW·h) | 1 kW*/h ≤ 0,375 l |
| Spremnik goriva / Fuel tank capacity (L) | 65 l |
| Dozvoljeni kontinuirani rad / Continuous running time (h) | 11 h |